

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **09294765 A**

(43) Date of publication of application: **18.11.87**

(51) Int. Cl.

A61F 13/00

A61K 9/70

A61K 31/715

A61K 31/725

A61K 38/17

A61L 15/44

(21) Application number: **08134135**

(71) Applicant: **MIC KK**

(22) Date of filing: **02.05.96**

(72) Inventor: **SUZUKI SHIGEKI**

(54) **WOUND SURFACE PROTECTIVE SOLUBLE
HEMOSTATIC MATERIAL**

used for ordinary tacky adhesive tapes or coating or laminating this material like a film.

(57) Abstract:

COPYRIGHT: (C)1997,JPO

PROBLEM TO BE SOLVED: To make it possible to effectively stop the bleeding on a wound surface and to improve a wound treating effect by forming a soluble hemostatic material layer as a wound protective surface and laminating a sheet-like member for fixing via a tacky adhesive layer which is peelable and weakly tacky adhesive on the rear surface thereof.

SOLUTION: The soluble hemostatic material layer 2 of the wound surface protective soluble hemostatic the 1 is formed as the wound protective surface and the sheet-like member 4 for fixing is laminated via a tacky adhesive layer 3 which is peelable and weakly tacky adhesive on the rear surface thereof. The soluble hemostatic material layer 2 is obtd. by forming oxycellulose, collagen oxide, sodium cellulose, calcium alginate, etc., to a woven fabric, non-woven fabric or sponge form. Above all, S-99 hemostatic gauze is preferably laminated as the hemostatic material layer. The tacky adhesive layer 3 is formed by directly laminating a weakly tacky adhesive of a high-polymer compd. system of an acrylic system or silicon system

